

Listing of the Claims:

The following is a complete listing of all the claims in the application, with an indication of the status of each:

1 Claim 1 (Currently Amended). A connection structure, comprising:
2 a connector, having an inner side face defining a chamber formed
3 with an opening and having an outer side face opposed to the inner side
4 face;
5 a module body, inserted from the opening to be accommodated in
6 the chamber;
7 a first conductive member, provided on an outer periphery of the
8 module body which is opposed to the inner side face of the connector in a
9 case where the module body is accommodated in the chamber; **and**
10 a second conductive member, provided on the inner side face of the
11 connector, such that the first conductive member is brought into contact
12 with the ~~first~~ second conductive member in a case where the module body
13 is plenarily accommodated in the chamber, and
14 wherein the second conductive member is extended from the inner
15 side face to the outer side face so as to be connected to an external line at
16 the outer side face.

1 Claim 2 (Original). The connection structure as set forth in claim 1,
2 wherein the second conductive member is extended in a direction parallel
3 to an inserting direction of the module body.

1 Claim 3 (Original). The connection structure as set forth in claim 1,
2 wherein the module body is a memory module.

1 Claim 4 (Original). The connection structure as set forth in claim 1,
2 wherein the module body is a camera module.

1 Claim 5 (Original). The connection structure as set forth in claim 1,
2 wherein an end of the chamber opposite to the opening is made open.

1 Claim 6 (Original). The connection structure as set forth in claim 1,
2 wherein at least a pair of the second conductive member is arranged on the
3 inner side face of the connector so as to oppose to each other.

1 Claim 7 (Original). The connection structure as set forth in claim 6, wherein
2 the second conductive member has elasticity.

1 Claim 8 (new). The connection structure as set forth in claim 1, wherein a
2 plate is attached to the bottom face of the connector so as to reinforce the
3 module accommodated in the chamber.

1 Claim 9 (new). A connection structure, comprising:
2 a connector, having a top face and a bottom face opposed to the top
3 face, and having an inner side face defining a chamber communicating a
4 first opening formed in the top face and a second opening formed in the
5 bottom face;
6 a module body, having a top face and a bottom face opposed to the
7 top face, adapted to be accommodated in the chamber;
8 a first conductive member, provided on an outer periphery of the
9 module body which is opposed to the inner side face of the connector in a
10 case where the module body is accommodated in the chamber; and
11 a second conductive member, provided on the inner side face of the
12 connector, such that the first conductive member is brought into contact
13 with the second conductive member in a case where the module body is
14 plenarily accommodated in the chamber;
15 wherein the first opening has a same shape as the second opening.

1 Claim 10 (new). The connection structure as set forth in claim 9, wherein

2 the bottom face of the connector is coplanar with the bottom face of the
3 module body in a case where the module body is plenarily accommodated
4 in the chamber.

1 Claim 11 (new). The connection structure as set forth in claim 9, wherein a
2 plate is attached to the bottom face of the connector so as to reinforce the
3 module accommodated in the chamber.